

Application No.: 09/758,606

Filed: January 11, 2001

TC Art Unit: 2644

Confirmation No.: 9889

AMENDMENTS TO THE CLAIMS

1. (previously presented) A parametric audio system for generating at least one airborne audio beam, comprising:

at least one audio signal source configured to provide at least one audio signal;

at least one signal conditioner configured for receiving the at least one audio signal and for nonlinearly processing the audio signal to provide at least one pre-distorted signal;

a modulator configured to receive the pre-distorted signal and to convert the pre-distorted signal into ultrasonic frequencies; and

an acoustic transducer array including at least one acoustic transducer, the array being configured to receive the converted signal and to project the converted signal through the air along a selected path, thereby inverting distortion in the projected signal and regenerating the audio signal along at least a portion of the selected path with reduced net distortion,

wherein the acoustic transducer array has a bandwidth greater than 5 kHz.

2. (original) The parametric audio system of claim 1 wherein each acoustic transducer is a membrane-type transducer.

-2-

WEINBAUER, SCHUBERT,  
GAGNEBIN & LEDOVICI LLP  
TEL. (617) 541-2290  
FAX. (617) 451-0313

Application No.: 09/758,606

Filed: January 11, 2001

TC Art Unit: 2644

Confirmation No.: 9889

3. (original) The parametric audio system of claim 2 wherein the membrane-type transducer is a Sell-type electrostatic transducer.

4. (original) The parametric audio system of claim 2 wherein the membrane-type transducer further includes a conductive membrane, a backplate electrode, and a DC bias source between the conductive membrane and the backplate electrode.

5. (previously presented) The parametric audio system of claim 4 further including

at least one driver amplifier coupled between the modulator and the acoustic transducer array and configured to receive the converted signal and to generate an amplified signal representative of the converted signal, and

a blocking capacitor coupled between the driver amplifier and the acoustic transducer array and configured to block the DC bias from the driver amplifier.

6. (previously presented) The parametric audio system of claim 4 further including

Application No.: 09/758,606

Filed: January 11, 2001

TC Art Unit: 2644

Confirmation No.: 9889

at least one driver amplifier coupled between the modulator and the acoustic transducer array and configured to receive the converted signal and to generate an amplified signal representative of the converted signal, and

a first component coupled between the acoustic transducer array and the DC bias source and configured to block the amplified signal from the DC bias source.

7. (original) The parametric audio system of claim 4 wherein the DC bias source is provided by an embedded charge.

8. (original) The parametric audio system of claim 3 wherein the Sell-type electrostatic transducer includes a conductive membrane, a backplate electrode, and a dielectric spacer disposed between the conductive membrane and the backplate electrode.

9. (original) The parametric audio system of claim 2 wherein the membrane-type transducer is a Sell-type electrostatic transducer including a conductive membrane, an electrode, and an insulative backplate disposed between the conductive membrane and the electrode.

Application No.: 09/758,606

Filed: January 11, 2001

TC Art Unit: 2644

Confirmation No.: 9889

10. (previously presented) The parametric audio system of claim 1 wherein the signal conditioner is configured to perform nonlinear inversion of the audio signal to generate the pre-distorted signal.

11. (currently amended) The parametric audio system of claim 1 further including

at least one driver amplifier coupled between the modulator and the acoustic transducer array and configured to receive the converted signal,

wherein the converted signal is an undivided signal,

wherein the driver amplifier is further configured and to generate an amplified signal representative of the undivided converted signal, and

a matching filter configured to compensate for a non-flat frequency response of the combination of the acoustic transducer array and the driver amplifier.

12. (original) The parametric audio system of claim 1

wherein the at least one acoustic transducer comprises a membrane-type transducer,

Application No.: 09/758,606

Filed: January 11, 2001

TC Art Unit: 2644

Confirmation No.: 9889

wherein the membrane-type transducer has a loudness figure of merit,  $l$ , defined according to the expression  $l = (\text{Area}) \cdot (\text{Amplitude})^2$ , and

wherein "Area" is the area of the membrane-type transducer and "Amplitude" is the amplitude of the modulated carrier signal.

13. (original) The parametric audio system of claim 12 wherein " $l$ " is greater than  $(2.0 \times 10^4) \text{ Pa}^2 \cdot \text{in}^2$ .

14. (original) The parametric audio system of claim 12 wherein " $l$ " is greater than  $(4.5 \times 10^5) \text{ Pa}^2 \cdot \text{in}^2$ .

15. (currently amended) ~~A The parametric audio system of claim 1 further including for generating at least one airborne audio beam, comprising:~~

~~— at least one audio signal source configured to provide at least one audio signal;~~

~~— at least one signal conditioner configured for receiving the at least one audio signal and for nonlinearly processing the audio signal to provide at least one pre distorted signal;~~

Application No.: 09/758,606

Filed: January 11, 2001

TC Art Unit: 2644

Confirmation No.: 9889

~~a modulator configured to receive the pre-distorted signal and to modulate an ultrasonic carrier signal with the pre-distorted signal,~~

at least one driver amplifier configured to receive the modulated carrier signal and to generate an amplified signal representative of the modulated carrier signal; and,

~~an acoustic transducer array including at least one acoustic transducer, the array being configured to receive the modulated carrier signal and to project the modulated carrier signal through the air along a selected path, thereby demodulating the modulated carrier signal and inverting distortion in the projected signal to regenerate the audio signal along at least a portion of the selected path with reduced net distortion,~~

wherein the driver amplifier includes an inductor coupled to a capacitive load of the acoustic transducer array to form a resonant circuit having a resonance frequency approximately equal to the frequency of the ultrasonic carrier signal.

16. (original) The parametric audio system of claim 15 wherein the frequency of the ultrasonic carrier signal is greater than or equal to 45 kHz.

Application No.: 09/758,606

Filed: January 11, 2001

TC Art Unit: 2644

Confirmation No.: 9889

17. (original) The parametric audio system of claim 15 wherein the frequency of the ultrasonic carrier signal is greater than or equal to 55 kHz.

18. (original) The parametric audio system of claim 15 wherein the driver amplifier further includes a damping resistor coupled between the inductor and the capacitive load of the acoustic transducer array.

19. (original) The parametric audio system of claim 15 wherein the driver amplifier further includes a step-up transformer and the inductor is provided by the step-up transformer.

20. (currently amended) A parametric audio system for generating at least one airborne audio beam, comprising:

at least one audio signal source configured to provide at least one audio signal;

at least one signal conditioner configured for receiving the at least one audio signal and for nonlinearly processing the audio signal to provide at least one pre-distorted signal;

Application No.: 09/758,606

Filed: January 11, 2001

TC Art Unit: 2644

Confirmation No.: 9889

a modulator configured to receive the at least one pre-distorted signal and to convert the pre-distorted signal into ultrasonic frequencies;

at least one driver amplifier configured to receive the at least one converted signal, wherein the at least one converted signal is an undivided signal, the at least one driver amplifier being further configured and to generate at least one amplified signal representative of the undivided converted signal;

an acoustic transducer array including a plurality of acoustic transducers, the array being configured to receive the at least one ~~converted-amplified~~ amplified signal and to project the ~~converted~~ amplified signal through the air for inverting distortion in the projected signal and for subsequent regeneration of the audio signal with reduced net distortion; ~~and~~

a matching filter configured to compensate for a non-flat frequency response of the combination of the acoustic transducer array and the driver amplifier; and

a delay circuit configured to apply at least one predetermined time delay to the at least one converted signal.

21. (previously presented) The parametric audio system of claim 20 wherein the delay circuit is configured to apply the at least



Application No.: 09/758,606

Filed: January 11, 2001

TC Art Unit: 2644

Confirmation No.: 9889

one predetermined time delay to the at least one converted signal to steer the converted signal through the air along at least one path by the acoustic transducer array.

22. (original) The parametric audio system of claim 20 wherein the acoustic transducer array further includes a membrane disposed along an adjacent backplate, the backplate including a plurality of depressions formed on a surface thereof, and each acoustic transducer being defined by the membrane and one or more of the depressions.

23. (original) The parametric audio system of claim 22 wherein the dimensions of the respective depressions are set to determine the center frequency and the bandwidth of the respective acoustic transducers.

24. (original) The parametric audio system of claim 20 wherein the delay circuit is configured to apply a predetermined time delay,  $d$ , according to the expression  $d = (x \cdot \sin(\theta))/c$ , wherein "x" is the distance from a datum to a respective acoustic transducer and "c" is the speed of sound.

-10-

WEINGARTEN, SCHURGIN,  
GAGNEBIN & LEBOVICI LLP  
TEL. (617) 542-2250  
FAX. (617) 451-0313

Application No.: 09/758,606

Filed: January 11, 2001

TC Art Unit: 2644

Confirmation No.: 9889

25. (currently amended) An acoustic transducer array, comprising:  
a backplate including a surface and a plurality of respective depressions of varying dimensions formed on the surface; and  
a membrane adjacently disposed along the backplate,  
wherein the membrane and at least one of the plurality of respective depressions define at least one acoustic transducer,  
and

wherein the dimensions of the respective depressions are set to determine the center frequency and the bandwidth of the at least one acoustic transducer,

wherein the acoustic transducer array has a bandwidth greater than 5 kHz.

26. (canceled)

27. (previously presented) The parametric audio system of claim 15 wherein the at least one acoustic transducer is a membrane-type transducer.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**